



DGD、EGS系列手轮机构
DGD & EGS Series Gear Box



无锡市圣汉斯控制系统有限公司
Wuxi St.Hans Controls Co.,Ltd.



◆工厂介绍 Company Introduction



圣汉斯致力于为广大客户提供更好的产品和服务，帮助客户提高工作效率，确保产品的使用安全，不断的研发和更新产品。

我们正努力地为您提供卓越的技术，更多的创新和最高的质量标准，从执行器机构到手轮机构以及其他的气动附件。

我司最新研制，生产制造的手轮机构在各式阀门中得到广泛运用，在安装调试，气源故障等恶劣工况下成为不可缺少的工作部件之一。

Focusing on the mindset to provide better products and services to customers, to improve customer work efficiency and ensure the safe use of product, STHANS-CONTROLS devotes to develop and update products continuously.


We are striving to provide you excellent technology, more innovative products and higher quality standards for the actuator mechanism, handwheel and other pneumatic accessories.

Our newly developed handwheel mechanism is widely used in various valves. It has also become one of the indispensable component for installation debugging and air supply failure under severe working conditions.




◆ 手轮机构主要特点 Main Features

- 结构紧凑，个性化多项设计可选
- 易操作
- 结构合理，故障率低
- 材质可选，适合各种环境
- 开位、关位 $\pm 5^\circ$ 可调
- 防护等级可达到IP67
- 工作温度：
 - 标准型：-20℃-- +80℃
 - 低温型：-40℃-- +80℃
 - 高温型：-15℃-- +120℃
- 上下安装法兰符合ISO5211标准
- DGD手轮机构手自动离合切换，适合单、双作用执行器
- EGS手轮机构无须切换，专门为单作用设计，更加安全可靠
- DGD系列可选自动泄压阀/平衡阀
- 规格多，输出扭矩范围广
- 表面处理可选，喷漆或环氧树脂喷涂
- Compact structure, individual and diversified design
- Easy operation
- Reasonable structure, low failure rate
- Materials alternative, applicable for various environments
- $\pm 5^\circ$ adjustment at both open and close directions easily and precisely.
- Enclosure: Sealed to IP67
- Operating temperature:
 - Standard: -20℃~+80℃
 - Low temperature: -40℃~+80℃
 - High temperature: -15℃~+120℃
- The upper and lower mounting flanges conform to ISO5211
- DGD gear box hand automatic clutch switch, applicable for both spring and double acting actuators
- EGS gear box without switching, special design for single acting actuators, more safety and reliable
- DGD series of optional automatic pressure relief valve or equalising valve
- Broad Specifications, Wide range of output torque
- Surface Treatment Optional: painted or powder polyester painted






◆ DGD系列手轮机构 DGD Series Gear Box



材料表 Materials


序号 No.	零件名称 Name	材料 Materials	备注 Remarks
1	上壳体 Cap	铝合金 Aluminium Alloy	DGD025~100铝合金 DGD025~100Aluminium Alloy
		球墨铸铁 Ductile Iron	DGD200~DGD400球墨铸铁 DGD200~DGD400Ductile Iron
2	下壳体 Body	铝合金 Aluminium Alloy	DGD025~100铝合金 DGD025~100Aluminium Alloy
		球墨铸铁 Ductile Iron	DGD200~DGD400球墨铸铁 DGD200~DGD400Ductile Iron
3	调整螺栓 Adjust screws	碳钢 Carbon Steel	
4	蜗轮 Worm gear	球墨铸铁 Ductile Iron	
5	蜗杆组件 Worm	碳钢、球墨铸铁 Carbon Steel/Ductile Iron	
6	切换手柄 Switch handle	碳钢 Carbon Steel	
7	压盖 Gland	碳钢 Carbon Steel	
8	手轮盘 Hand wheel	碳钢 Carbon Steel	可选材质:铸铁 Optional material: Iron

外型尺寸 Dimensions (without shaft)



型号 Model	A	B	C	ØD	ØE1	ØE2	F1	F2	G	H	J	K	L	M1	M2	F3	F4	ØN
DGD025	102	145	167	140	7	9	50	70	63	120	44	8	30.8	M6	M8	50	70	28
DGD050	125	166	230	280	—	11	—	102	82	143	45	10	41.3	M8	M10	70	102	38
DGD100	174	207	284	350	—	13	—	125	83	150	52	14	49.8	M10	M12	102	125	46
DGD200	234	267	359	400	18	22	140	165	101	173	48	18	64.4	M16	—	140	—	60
DGD201	234	267	359	500	18	22	140	165	101	173	48	18	64.4	—	M20	—	165	60
DGD400	292	325	425	600	—	22	—	165	125	186	38	22	77.4	—	M20	—	165	72
DGD800	438	385	463	500	8-Ø18	—	254	—	164	248	57	20	79.9	8-M16	—	254	—	75

含轴尺寸表 Dimensions (with shaft)



Model	R	S	T	U
DGD025	17	20	19	17
DGD050	22	25	24	22
DGD100	27	30	29	27
DGD200	36	39	38	36

Model	R	S	T	U
DGD201	46	49	38	36
DGD400	46	50	48	46
DGD800	55	60	57	55

◆ EGS系列手轮机构 EGS Series Gear Box




材料表 Materials

序号 No.	零件名称 Name	材料 Materials	备注 Remarks
1	上壳体 Cap	铝合金 Aluminium Alloy	EGS050~100铝合金 EGS050~100Aluminium Alloy
		球墨铸铁 Ductile Iron	EGS200~400球墨铸铁 EGS200~400Ductile Iron
2	下壳体 Body	铝合金 Aluminium Alloy	EGS050~100铝合金 EGS050~100Aluminium Alloy
		球墨铸铁 Ductile Iron	EGS200~400球墨铸铁 EGS200~400Ductile Iron
3	调整螺栓 Adjust screw	碳钢 Carbon Steel	
4	蜗轮 Worm gear	球墨铸铁 Ductile Iron	
5	蜗杆组件 Worm	碳钢、球墨铸铁 Carbon Steel/Ductile Iron	
6	手轮盘 Hand wheel	碳钢 Carbon Steel	可选材质: 铸铁 Optional material: Iron



外型尺寸 Dimensions (without shaft)



型号 Model	A	B	C	ØD	ØE1	ØE2	F1	F2	G	H	J	K	M1	M2	F3	F4	ØN	key
EGS050	106	155	230	350	9	11	70	102	58	120	48	41.3	M8	M10	70	102	38	10
EGS100	154	195	284	400	—	13	—	125	82	135	53	49.8	M10	M12	102	125	46	14
EGS200	234	260	359	500	18	22	140	165	100	152	36	64.4	M16	—	140	—	60	18
EGS201	234	260	359	500	18	22	140	165	100	152	36	64.4	—	M20	—	165	60	18
EGS400	293	304	292	900	—	22	—	165	118	175	28	77.4	—	M20	—	165	72	22

含轴尺寸表 Dimensions (with shaft)

Technical drawings of the ALPHA EGS series actuators showing front, side, and top views with dimension labels R, S, T, and U.

Model	□R	S	T	□U
EGS050	22	25	24	22
EGS100	27	30	29	27
EGS200	36	39	38	36

Model	□R	S	T	□U
EGS201	46	49	38	36
EGS400	46	50	48	46

◆ 可选配组件

Optional Components

- 手轮盘 Hand Wheel





球墨铸铁件 Iron Casting




冲压件 Stamping


• 传动轴 Shaft



• 泄压阀 Vent valve



• 平衡阀 Equalising valve



◆ MG系列
Manual Gear



◆订购信息 How to order

UNIT 单元	1	2	3	4	5	6	7	Product code 产品代号
CONTENT 内容	DGD	050	1	1	1	0	2	DGD050-11102
EXPLAIN 说明	Series 系列	输出扭矩 Output Torque	泄压阀 Vent Valve	传动轴 Shaft	铸造型手轮盘 Cast iron hand wheel	表面黑色 Black	低温型 Low TEMP	

DGD	离合式手轮机构 Dec clutchable gear box for DA/SR	025 250Nm 050 500Nm 100 1000Nm	0 不含中轴 without shaft 1 含中轴 with shaft	0 冲压手轮盘 Stamping hand wheel 1 铸造型手轮盘 Cast iron hand wheel	0 常温型 Standard TEMP 1 高温型 High TEMP 2 低温型 Low TEMP
EGS	单作用手轮机构 Emergency gear box for SR	200 2000Nm 201 2000Nm 400 4000Nm 800 8000Nm			
MG	手动齿轮箱 Manual Gear				

0	不含泄压阀等 No Vent Valve etc.
1	泄压阀 Vent Valve
2	平衡阀 Equalising Valve

0	黑色 Black
1	红色 Red
2	客户颜色 Custom color



无锡市圣汉斯控制系统有限公司
Wuxi St.Hans Controls Co.,Ltd.

地址：无锡市新区金城东路529号 邮编(P.C.): 214112

Add : No.529, Jincheng East Road, New District, Wuxi City, China

电话(Tel): 0086-510-81150895/96/97 85213820

传真(Fax): 0086-510-85227486

E-mail: sales@sthans-controls.com Http:// www.sthans-controls.com